



SLINGSHOT LLC

www.slingshotwholesale.com

PHONE: 304.375.2553

FAX: 304.375.2217

COMPANY: _____

CONTACT: _____

JOB NAME: _____

PHONE: _____

FAX: _____

E-MAIL: _____

Storefront Take-Off Guide

Data Sheet: SF10.3.1

3-2010

1. FINISH:

___ CLEAR ANO., ___ BRONZE ANO., OTHER: _____

2. FRAMING: (JAMB DEPTH TO BE 4 1/2")

- ___ 2" FRAME FACE (FOR 1" INSULATED GLASS)
- ___ 1 3/4" FRAME FACE (FOR 1/4" GLASS)

3. GLAZING: (STOREFRONT WINDOW(S))

- ___ 1/4" NON-INSULATED
- ___ 1" INSULATED GLASS
- ___ CLEAR TEMPERED (std.)
- ___ TEMPERED LOW E (for 1" i.g. only)
- ___ TINTED
- ___ OTHER: _____

4. ENTRANCE (S): (ALL DOORS TO BE 1 3/4" THICK)

___ NARROW (std.), ___ MEDIUM, ___ WIDE

5. HARDWARE:

___ PUSH/ PULL (std.), ___ PANIC DEVICE

6. GLAZING: (DOOR(S))

- ___ 1/4" NON-INSULATED (std.)
- ___ 1" INSULATED GLASS
- ___ CLEAR TEMPERED (std.)
- ___ TEMPERED LOW E (for 1" i.g. only)
- ___ TINTED
- ___ OTHER: _____

SKETCH THE REQUIRED OPENING(S) BELOW. (OR ATTACH DRAWINGS) INCLUDE DIMENSIONS

